

IDROBASE[®]

PASSION FOR WATER

 **NEW!**

 EN

PROFESSIONAL H.P. WASHERS

Coccinella evo



>1450
Rpm
50Hz



Technical features

- **Frame set** made of chromed steel
- **Cover** made of thermoformed polystyrene
- **Professional pump** 1450Rpm, crankshaft, brass head, 3 ceramic plungers. Complete with bolt unloader valve, detergent injector and glycerine-filled pressure gauge
- **Electric motor** 1450Rpm 50Hz, complete with ON/OFF, circuit breaker switch and 5m electric cable
- **Dimensions WxLxH:** 440 x 667 x 950mm

Standard equipment









- **H.p. hose** 8m, with screw quick couplings M22x1,5 M
- **Spray gun with extension** inlet M22x1,5 M
- **580mm lance extension**
- **H.p. nozzle** 25° high resolution

Code	Model	Version	Pressure	Flow rate	Rpm	Power	Weight
With Interpump pump							
ZX.2560-TS	E1 130/9 TS	Total Stop	130bar	9l/min	1450	3,0hp/2,2kW (1x230V-50Hz)	44kg
ZX.2561-TS	E1 160/11 TS	Total Stop	160bar	11l/min	1450	5,5hp/4,0kW (3x400V-50Hz)	44kg












Spare parts

Code	Description	ZX.2560-TS	ZX.2561-TS
ZX.IP008	Repair set for pump ZX.SPI008 - seals, valves and plunger oil seals (quantity 10x3)		●
ZX.IP009	Repair set for pump ZX.SPI009 - seals, valves and plunger oil seals (quantity 10x3)	●	
ZX.1966	Service kit by-pass valve	●	●
ZX.15W40-1	SAE 15W 40 mineral oil 1L Ideal for high pressure pumps	●	●

Optional

NEW!	Code	Description	ZX.2560-TS	ZX.2561-TS
	CDR.7735-M22	High pressure filter M22x1,5 M-F, to be connected to the pump outlet to stop the micro impurities		
	ZX.0988-L-P	Foam lance with brass body, POM delivery with screw quick coupling M22x1,5 M long	•	•
	ZN.AC100X2P2P	H.p. hose R1 1/4", 210bar, 10m, M22x1,5 F-F	•	
	ZN.CC100B3P3P	H.p. hose R1 5/16", 315bar, 10m, M22x1,5 F-F		•
	ZN.AC200X2P2P	H.p. hose R1 1/4", 210bar, 20m, M22x1,5 F-F	•	
	ZN.CC200B3P3P	H.p. hose R1 5/16", 315bar, 20m, M22x1,5 F-F		•
	CDR.7062	Hose connection M22x1,5 M-M	•	•
	ZX.2127	Hose reel kit composed of: chromed support, manual hose reel and connection hose	•	•
	ZY.030-T6M	Terminal with rotating nozzle - 030	•	•
	ZX.MMC101	Hose for sewer nozzles 3/16" 10m M22x1,5 M - 030	•	•
	ZS.030-T6M	Terminal with sandblasting head - 030	•	•

Do it yourself

	Code	Description	 	
			ZX.2560-TS	ZX.2561-TS
	ZX.1961	Frame set made of chromed steel with wheels, size 650x370x940mm	•	•
	ZX.0234	Grey cover complete with fixing screws for frame set ZX.1961	•	•
	ME.M001	Electric motor 3,0hp/2,2kW H100 C90, 1450Rpm, 1x230V - 50Hz	•	
	ME.T029	Electric motor 5,5hp/4,0kW H100 C90, 1450Rpm, 3x400V - 50Hz		•
	ZX.12XE	Electrical box 1x230V 50/60Hz with 14A switch and 5m power supply cable	•	
	ZX.14EH	Electrical box 3x400V 50/60Hz with 12A switch, Total Stop device and 5m power supply cable		•
	ZX.SPIP008	Pump set 160bar, 11l/min, 1450Rpm, complete with by-pass valve, pressure gauge and inlet water filter (110/11 with 3,0kW - 160/11 with 5,5kW)		•
	ZX.SPIP009	Pump set 180bar, 9l/min, 1450Rpm, complete with by-pass valve, pressure gauge and inlet water filter (130/9 with 3,0kW - 180/9 with 5,5kW)	•	
	ZP.E4H	ECO 1 spray gun with extension, M22x1,5 M-F	•	•
	ZD.25030-T6M	Lance extension 580mm con ugello 25° 030, inlet M22x1,5 M	•	•
	ZN.AC080X2P2P	H.p. hose R1 1/4" 210bar 8m, M22x1,5 F-F	•	
	ZN.CC080B3P3P	H.p. hose R1 5/16" 315bar 8m, M22x1,5 F-F		•



Scarabeo evo



>1450 Rpm 50Hz



Technical features

- **Professional pump** with crankshaft, brass head, 3 ceramic plungers. Complete with bolt unloader valve, pressure gauge and water inlet filter
- **Electric motor** complete with electric box IP55 and with ON/OFF circuit breaker switch
 - 5m **electric cable**

Motor-pump unit

Professional motor-pump unit **pre-assembled** and **tested**.

Code	Model	Version	Pressure	Flow rate	Rpm	Power	Inlet
With Interpump pump							
ZX.2860-TS	1450 130/9 TS	Total Stop	130bar	9l/min	1450	3,0hp/2,2kW (1x230V-50Hz)	M22x1,5 M
ZX.2861-TS	1450 160/11 TS	Total Stop	160bar	11l/min	1450	5,5hp/4,0kW (3x400V-50Hz)	M22x1,5 M

Spare parts

Code	Description	ZX.2860-TS	ZX.2861-TS
ZX.IP008	Pump set composed by seals, valves and plunger oil seals (quantity 10x3)		●
ZX.IP009	Pump set composed by seals, valves and plunger oil seals (quantity 10x3)	●	
ZX.1966	Service kit by-pass valve	●	●
ZX.15W40-1	SAE 15W 40 mineral oil, ideal for high pressure pumps, 1L	●	●

Optionals

Code	Description	ZX.2860-TS	ZX.2861-TS
CDR.7735-M22	High pressure filter M22x1,5 M-F, to be connected to the pump outlet to stop the micro impurities	●	●
ZX.1968	Supporting kit for motor-pump unit composed by 2 chromed support brackets and 6 anti-vibration feet	●	●
ZL.XEXN	ECO1 spray gun: M22x1,5 M inlet with 900mm lance and 25° 030 nozzle	●	●
ZL.1FKQ	A-Kit Lavaggio PROFY composed by ECO1 spray gun with M22x1,5 M inlet, 700mm lance with M inlet KW type and foam lance with M inlet KW type	●	●
ZN.AC080X2P2P	H.p. hose R1 1/4" 210bar 8m, M22x1,5 F-F	●	
ZN.AC100X2P2P	H.p. hose R1 1/4" 210bar 10m, M22x1,5 F-F	●	
ZN.AC150X2P2P	H.p. hose R1 1/4" 210bar 15m, M22x1,5 F-F	●	
ZN.AC200X2P2P	H.p. hose R1 1/4" 210bar 20m, M22x1,5 F-F	●	
ZN.CC080B3P3P	H.p. hose R1 5/16" 315bar 8m, M22x1,5 F-F		●
ZN.CC100B3P3P	H.p. hose R1 5/16" 315bar 10m, M22x1,5 F-F		●
ZN.CC150B3P3P	H.p. hose R1 5/16" 315bar 15m, M22x1,5 F-F		●
ZN.CC200B3P3P	H.p. hose R1 5/16" 315bar 20m, M22x1,5 F-F		●

Scarabeo evo




Total stop



MADE IN ITALY




>1450 Rpm 50Hz



Technical features

- **Professional pump** with crankshaft, brass head, 3 ceramic plungers. Complete with bolt unloader valve, pressure gauge and brass water inlet filter
- **Electric motor** complete with electric box IP55 and with ON/OFF circuit breaker switch
- 5m **electric cable**

Motor-pump unit

Professional motor-pump unit **pre-assembled** and **tested**.

Code	Model	Version	Pressure	Flow rate	Rpm	Power	Inlet
With Interpump pump							
ZX.2862-TS	1450 200/14 TS	Total Stop	200bar	14l/min	1450	7,5hp/5,5kW (3x400V-50Hz)	M22x1,5 M
ZX.2863-TS	1450 250/15 TS	Total Stop	250bar	15l/min	1450	10,0hp/7,5kW (3x400V-50Hz)	M24x1,5 M

Spare parts

Code	Description	ZX.2862-TS	ZX.2863-TS
ZX.IP002	Pump set composed by seals, valves and plunger oil seals	•	
ZX.IP003	Pump set composed by seals, valves and plunger oil seals		•
ZX.1977	Service kit by-pass valve	•	•
ZX.15W40-1	SAE 15W 40 mineral oil, ideal for high pressure pumps, 1L	•	•

Optionals

Code	Description	ZX.2860-TS	ZX.2861-TS
CDR.7735-M22	High pressure filter M22x1,5 M-F, to be connected to the pump outlet to stop the micro impurities	•	•
ZX.1968	Supporting kit for motor-pump unit composed by 2 chromed support brackets and 6 anti-vibration feet	•	•
ZL.XGXR	RED60 spray gun: M22x1,5 M inlet with 900mm lance and 25° 040 nozzle	•	
ZX.XHXR	RED60 spray gun: M24x1,5 M inlet with 900mm lance and 25° 040 nozzle		•
ZL.1LKS	A-Kit Lavaggio PROFY composed by RED60 spray gun with M22x1,5 M inlet, 700mm lance with M inlet KW type and foam lance with M inlet KW type	•	
ZN.CC080B3P3P	H.p. hose R1 5/16" 315bar 8m, M22x1,5 F-F	•	
ZN.CC100B3P3P	H.p. hose R1 5/16" 315bar 10m, M22x1,5 F-F	•	
ZN.CC150B3P3P	H.p. hose R1 5/16" 315bar 15m, M22x1,5 F-F	•	
ZN.CC200B3P3P	H.p. hose R1 5/16" 315bar 20m, M22x1,5 F-F	•	
ZX.2052	H.p. hose R2 5/16" 350bar 8m, M24x1,5 F-F		•
ZX.2056	H.p. hose R2 5/16" 350bar 10m, M24x1,5 F-F		•
ZX.2057	H.p. hose R2 5/16" 350bar 15m, M24x1,5 F-F		•
ZX.2058	H.p. hose R2 5/16" 350bar 20m, M24x1,5 F-F		•



idrobase[®]

idrobase.com



club dei riparatori[®]

clubdeiriparatori.com



enjoyyourfurniture.com



idrotech[®]

idrotech.com



club del misting[®]

clubdelmisting.com

Idrobase Group s.r.l.

35010 BORGORICCO (PD) ITALIA - Via dell'Industria, 25

+39 049 9335903 +39 049 9335922

info@idrobasegroup.com



Certification de qualité
n° 9.160 -IDR3 - 30/10/1998
UNI ES ISO 9001:2008

